

Technical Specifications

Specifications	FRM-01	FRM-02S
Operation Voltage (Un)	230 V AC	230 V AC
Operation Voltage Interval (U)	150-300 V AC	150-300 V AC
Operation Frequency	50 Hz	50 Hz
Power Consumption (Max)	2.5 VA	2.5 VA
Lux adjustment	1...10	1...10
Sleep Adjustment	None	3-10 hours Set/Sleep off
Off-Delay (Release delay)	30 sec fixed	1...60 sec Set
On-Delay (Draw delay)	30 sec fixed	1...60 sec Set
Setting Accuracy	+ or -5%	+ or -5%
Exit Relay	5 A 250 V AC	5 A 250 V AC
Operation Temperature	Between -20°C...50°C	Between -20°C...50°C
Relative Humidity	Less than 90% (Without condensation)	Less than 90% (Without condensation)
Cable Sections	2.5 mm ² multi vessel cable	2.5 mm ² multi vessel cable
Assembly Types	Rail type	Rail type
Protection Class	IP20 (Terminals), IP40 (Front Panel)	IP20 (Terminals), IP40 (Front Panel)
Dimensions	36x90x61	36x90x61
Weight	125gr	125gr
Insulation	400 V insulation voltage 4 KV source impact	400 V insulation voltage 4 KV source impact