

Termik Manyetik Motor Koruma Şalterleri

Kod No	Anma Gücü AC3 400V (kW), 50/60Hz	Termik Ayar Sahası [A] (40°)	Kısa Devre Kesme Kapasitesi Icu(KA) 400V-415V	Kutu Adet	Koli Adet	Brüt Ağırlık (kg)	Koli Ebat (mm)
69000001	0,02	0,10-0,16	100 kA	1	50	14,21	480 x 255 x 180
69000002	0,06	0,16-0,25	100 kA	1	50	14,21	480 x 255 x 180
69000003	0,09	0,25-0,40	100 kA	1	50	14,21	480 x 255 x 180
69000004	0,12	0,40-0,63	100 kA	1	50	14,21	480 x 255 x 180
69000005	0,25	0,63-1,00	100 kA	1	50	14,21	480 x 255 x 180
69000006	0,37	1,00-1,60	100 kA	1	50	14,21	480 x 255 x 180
69000007	0,75	1,60-2,5	100 kA	1	50	14,21	480 x 255 x 180
69000008	1,5	2,5-4	100 kA	1	50	14,21	480 x 255 x 180
69000009	2,2	4-6,3	100 kA	1	50	14,21	480 x 255 x 180
69000010	4	6-10	100 kA	1	50	14,21	480 x 255 x 180
69000011	5,5	9-14	15 kA	1	50	14,21	480 x 255 x 180
69000012	7,5	13-18	15 kA	1	50	14,21	480 x 255 x 180
69000013	9	17-23	15 kA	1	50	14,21	480 x 255 x 180
69000014	11	20-25	15 kA	1	50	14,21	480 x 255 x 180
69000015	15	24-32	10 kA	1	50	14,21	480 x 255 x 180



Motor Koruma Şalteri

Ürün Tanımı	Kod No	Teknik Özellik	Kutu Adet	Koli Adet	Brüt Ağırlık (kg)	Koli Ebat (mm)
-------------	--------	----------------	--------------	--------------	----------------------	-------------------

Aksesuarlar

Muhafaza Kutusu (Boş)	67000053	-	1	50	13,696	500 x 500 x 315
Yardımcı Kontak (soldan montaj)	67000054	1NA +1NK	1	100	5,59	467 x 200 x 157
Yardımcı Kontak (önden montaj)	67000055	1NA +1NK	4	400	9,59	467 x 200 x 157
Yardımcı Kontak (sağdan montaj)	67000056	1NA +1NK	1	100	???	???
Açtırma Bobini	67000057	220 V AC	1	50	5,981	465 x 290 x 74
Düşük Gerilim Bobini	67000058	220V AC	1	50	6,181	465 x 290 x 74
Alarm çıkış kontağı	67000059	1NA +1NK	1	100	5,49	467 x 200 x 157



Muhafaza Kutusu



Düşük Gerilim
Bobini



Açtırma Bobini



Alarm Çıkış
Kontağı



Yardımcı Kontak
(Soldan Montaj)



Yardımcı Kontak
(Önden Montaj)