

Technical Specifications

Specifications	V3T - 21	M3T - 22	M6T - 22C
Operating voltage	24V-300V AC/DC	24V-300V AC/DC	24V-300V AC/DC
Operating frequency	50/60Hz	50/60Hz	50/60Hz
Temperature range	-10 C° / +70 C°	-10 C° / +70 C°	-10 C° / +70 C°
Supply power consumption	< 6 VA	< 6 VA	< 6 VA
Class	%1 ±1 digit	%1 ±1 digit	%1 ±1 digit
Outputs relay	1 piece NO 5A 250V	2 piece NO 5A 250V	2 piece NO 5A 250V
Safety class	IP20	IP20	IP20
Cable thickness for terminal connection	2,5mm ²	2,5mm ²	2,5mm ²
Weight	< 300g	< 300g	< 300g

Specifications	M3T - 22C	M3T - 21	M3T - 20
Operating voltage	24V-300V AC/DC	24V-300V AC/DC	24V-300V AC/DC
Operating frequency	50/60Hz	50/60Hz	50/60Hz
Temperature range	-10 C° / +70 C°	-10 C° / +70 C°	-10 C° / +70 C°
Supply power consumption	< 6 VA	< 6 VA	< 6 VA
Class	%1 ±1 digit	%1 ±1 digit	%1 ±1 digit
Outputs relay	2 piece NO 5A 250V	1 piece NO 5A 250V	-
Safety class	IP20	IP20	IP20
Cable thickness for terminal connection	2,5mm ²	2,5mm ²	2,5mm ²
Weight	< 300g	< 300g	< 300g

Technical Specifications

Specifications	A1M-10 / A1M-10T	A1M-11	V1M-10	V1M-11
Operating voltage	150-300V AC/DC	150-300V AC/DC	150-300V AC/DC	150-300V AC/DC
Operating frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Temperature range	-20 C° / +70 C°	-20 C° / +70 C°	-20 C° / +70 C°	-20 C° / +70 C°
Supply power consumption	4VA (max)	4VA (max)	4VA (max)	4VA (max)
Class	%1 ±1 digit	%1 ±1 digit	%1 ±1 digit	%1 ±1 digit
Outputs relay	-	1 Pcs NO 5A 250V	-	1 Pcs NO 5A 250 V
Safety class	IP20	IP20	IP20	IP20
Cable thickness for terminal connection	2,5mm ²	2,5mm ²	2,5mm ²	2,5mm ²
Weight	220g / 275g	235g	225g	240g

Multimeter / Ampermeter / Voltmeter

Product Name	Code No.	Piece in Box	Piece in Package	Gross Weight (kg)	Size of Package (mm)
V3T - 21	152050003	1	12	3,71	250 x 235 x 220
M3T - 22	152050001	1	12	4,14	250 x 235 x 220
M6T - 22C	152050004	1	12	4,17	250 x 235 x 220
M3T - 22C	152050002	1	12	4,17	250 x 235 x 220
M3T - 21	152050006	1	12	4,04	250 x 235 x 220
M3T - 20	152050005	1	12	3,88	250 x 235 x 220
A1M - 10	152070017	1	12	2,96	250 x 235 x 220
A1M - 11	152070018	1	12	3,12	250 x 235 x 220
A1M - 10 T	152070030	1	12	3,60	250 x 235 x 220
V1M - 10	152070019	1	12	3,02	250 x 235 x 220
V1M - 11	152070027	1	12	3,18	250 x 235 x 220